

Pressure transmitter-Low cost

BT-PT-1100
BROIL



Constructive characteristics

Material in contact: AISI316L
Case : AISI304L
Protection: IP65 / IP67
Weight: 0.40 Kg
Process connection: G1/4 or G1/2 or as on request

Functional characteristics

Pressure range: 0...0,25 / 0...2000 bar
Sensor class (included linearity and hysteresis): 0.25%/0.5%/1%
Compensate temp. range: -20..+100°C
Permitted temperature fluid: -20..+100 °C
Zero drift: = typical : 0.05% fs/10K
Sensibility drift: = typical : 0.05% fs/10K
Zero offset: =±0.5%FS
Max applicable pressure (without decay): 2 time FS
Resistance to bursting: 3 time FS

Electrical Characteristics

Output signal: 4..20 mA , 0..5 Vdc, 0..10 Vdc , other on request
Electrical connection: cables, DIN43650 , 4 pole connector , other on request
Power supplier: 12...30Vdc (current) , 15..30 Vdc (Voltage)
CE conformity: 89/336 CE (EN50082-1 e 2 EN50081-1 e 2); 97/23/CE :3.3 Ps<200 bar cat 1 - Ps=200 bar
Isolation resistance at 50 Vdc: >1000M \square
Response time(10..90%): =10mS

BROIL SENSOTEK INDUSTRIES,


I-195, GIDC-2 , MEHSANA-384002, STATE: GUJARAT, INDIA.

Pressure transmitter

BT-PT-1100

Mechanical dimensions

BROIL



Electrical connections

Electrical connections

	Terminal		
Power supply (output) 15..30Vdc (0..5-10Vdc)	Pin 1 (+) Pin 2 (-) Pin 3 (Out 0..5- 10Vdc)	Red (+) Yellow or black (-) white (Out 0..5- 10Vdc)	Pin 1 (+) Pin 2 (-) Pin 3 (Out 0..5- 10Vdc)
Power supply (output) 09..30Vdc (4..20 mA)	Pin 1 (+) Pin 2 (-)	Red(+) Giallo o Yellow or black (-)	Pin 1 (+) Pin 2 (-)
Draws			